



T Copper Cable Lug

1.Terminal Body: Copper

2.Plating: Tin



Part No.	Dimensions(mm)				
	ΦE	ΦD	W	B	L
T6-5	5.3	3.8	10.0	10.0	26.0
T6-6	6.4	3.8	10.0	10.0	26.0
T6-8	8.3	3.8	10.0	10.0	29.0
T6-10	10.5	3.8	10.0	10.0	29.0
T10-4	4.3	4.7	11.5	11.5	27.5
T10-5	5.3	4.7	11.5	11.5	27.5
T10-6	6.4	4.7	11.5	11.5	27.5
T10-8	8.3	4.7	11.5	11.5	30.5
T10-10	10.5	4.7	11.5	11.5	30.5
T10-12	13.2	4.7	11.5	11.5	34.0
T16-5	5.3	5.6	12.0	12.0	27.5
T16-6	6.4	5.6	12.0	12.0	27.5
T16-8	8.3	5.6	12.0	12.0	31.0
T16-10	10.5	5.6	12.0	12.0	32.0
T16-12	13.2	5.6	12.0	12.0	37.5
T25-6	6.4	7.1	13.5	13.5	34.0
T25-8	8.3	7.1	13.5	13.5	34.0
T25-10	10.5	7.1	13.5	13.5	37.0
T25-12	13.2	7.1	13.5	13.5	40.0
T35-6	6.4	8.2	16.0	16.0	39.0
T35-8	8.3	8.2	16.0	16.0	39.0
T35-10	10.5	8.2	16.0	16.0	43.0
T35-12	13.2	8.2	16.0	16.0	43.0
T35-14	14.5	8.2	16.0	16.0	48.0
T35-16	16.5	8.2	16.0	16.0	48.0
T40-6	6.4	9.0	17.0	17.0	44.0
T40-8	8.3	9.0	17.0	17.0	44.0
T40-10	10.5	9.0	17.0	17.0	44.0
T40-12	13.2	9.0	17.0	17.0	44.0
T50-6	6.4	9.5	20.0	20.0	45.0
T50-8	8.3	9.5	20.0	20.0	45.0
T50-10	10.5	9.5	20.0	20.0	49.0
T50-12	13.2	9.5	20.0	20.0	49.0
T50-14	14.5	9.5	20.0	20.0	54.0
T50-16	16.5	9.5	23.0	23.0	62.0
T50-20	21.0	9.5	23.0	23.0	68.0
T70-8	8.3	11.5	20.0	20.0	47.6
T70-10	10.5	11.5	20.0	20.0	51.6
T70-12	13.2	11.5	20.0	20.0	51.6
T70-14	14.5	11.5	20.0	20.0	62.6
T70-16	16.5	11.5	20.0	20.0	62.6
T70-20	21.0	11.5	20.0	20.0	62.6
T95-8	8.3	13.5	22.0	22.0	55.8

Part No.	Dimensions(mm)				
	ΦE	ΦD	W	B	L
T95-10	10.5	13.5	24.0	22.0	55.8
T95-12	13.2	13.5	24.0	22.0	55.8
T95-14	14.5	13.5	24.0	22.0	66.8
T95-16	16.5	13.5	24.0	22.0	66.8
T95-20	21.0	13.5	24.0	22.0	66.8
T120-10	10.5	15.6	28.0	27.0	71.5
T120-12	13.2	15.6	28.0	27.0	71.5
T120-14	14.5	15.6	28.0	27.0	71.5
T120-16	16.5	15.6	28.0	27.0	71.5
T120-20	21.0	15.6	28.0	27.0	71.5
T150-10	10.5	16.5	29.5	32.0	78.0
T150-12	13.2	16.5	29.5	32.0	78.0
T150-14	14.5	16.5	29.5	32.0	78.0
T150-16	16.5	16.5	29.5	32.0	78.0
T150-20	21.0	16.5	29.5	32.0	78.0
T185-10	10.5	18.4	33.0	34.0	84.0
T185-12	13.2	18.4	33.0	34.0	84.0
T185-14	14.5	18.4	33.0	34.0	84.0
T185-16	16.5	18.4	33.0	34.0	84.0
T185-20	21.0	18.4	33.0	34.0	84.0
T240-10	10.5	21.2	37.5	37.0	90.0
T240-12	13.2	21.2	37.5	37.0	90.0
T240-14	14.5	21.2	37.5	37.0	90.0
T240-16	16.5	21.2	37.5	37.0	90.0
T240-20	21.0	21.2	37.5	37.0	90.0
T300-10	10.5	23.4	40.8	40.0	96.0
T300-12	13.2	23.4	40.8	40.0	96.0
T300-14	14.5	23.4	40.8	40.0	96.0
T300-16	16.5	23.4	40.8	40.0	96.0
T300-20	21.0	23.4	40.8	40.0	96.0
T400-10	10.5	26.8	46.8	37.0	104.7
T400-12	13.2	26.8	46.8	37.0	104.7
T400-14	14.5	26.8	46.8	37.0	104.7
T400-16	16.5	26.8	46.8	37.0	104.7
T400-20	21.0	26.8	46.8	37.0	104.7
T500-10	10.5	29.8	54.0	46.5	115.5
T500-12	13.2	29.8	54.0	46.5	115.5
T500-14	14.5	29.8	54.0	46.5	115.5
T500-16	16.5	29.8	54.0	46.5	115.5
T500-20	21.0	29.8	54.0	46.5	115.5
T630-10	10.5	34.5	62.0	50.0	133.1
T630-12	13.2	34.5	62.0	50.0	133.1