


Long Barrel Copper Cable Lug

1. Material: copper-99.9% pure.
2. Operating Temperature: -55°C to 155°C due to oxygen-free copper
3. Surface: Tin plated.



Part No.	Dimensions (mm)						WIRE RANGE A.W.G./mm ²
	ΦE	ΦD	Φd	W	B	L	
TL10-6	6.4	6.9	4.7	11.9	19	35	8A.W.G. 10mm ²
TL10-8	8.3			13.5		38	
TL16-6	6.4	7.8	5.6	11.9	23	39	6A.W.G. 16mm ²
TL16-8	8.3			13.5		42	
TL16-10	10.5			16			
TL25-8	8.3	9.5	7.1	14	29	50	4A.W.G. 25mm ²
TL25-10	10.5			16		53	
TL25-12	13.2			18		56	
TL35-6	6.4	11	8.2	16.5	30	54	2A.W.G. 35mm ²
TL35-8	8.3					58	
TL35-10	10.5						
TL50-8	8.3	12.5	9.5	18	35	60	1/0 A.W.G. 50mm ²
TL50-10	10.5					64	
TL50-12	13						
TL70-8	8.3	15	11.5	21.5	38	70	2/0 A.W.G. 70mm ²
TL70-10	10.5						
TL70-12	13						
TL95-10	10.5	17	13.5	24.7	43	88	3/0 A.W.G. 95mm ²
TL95-12	13						
TL95-14	14.5						
TL95-16	16.5						
TL120-10	10.5	20	15.6	29	49	94	4/0 A.W.G. 120mm ²
TL120-12	13						
TL120-14	14.5						
TL120-16	16.5						

Part No.	Dimensions(mm)						WIRE RANGE A.W.G.mm ²
	ΦE	ΦD	Φd	W	B	L	
TL150-10	10.5	21	16.5	30.4	56	102	250/300MCM 150mm ²
TL150-12	13						
TL150-14	14.5						
TL150-16	16.5						
TL150-20	21						
TL185-10	10.5	23.6	18.4	34	63	113	300/350MCM 185mm ²
TL185-12	13						
TL185-14	14.5						
TL185-16	16.5						
TL185-20	21						
TL240-10	10.5	26.4	21.2	38.5	66	119	400/500MCM 240mm ²
TL240-12	13						
TL240-14	14.5						
TL240-16	16.5						
TL300-10	10.5	28.6	23.4	41.7	77	133	500/600MCM 300mm ²
TL300-12	13						
TL300-14	14.5						
TL300-16	16.5						
TL400-10	10.5	32.8	26.8	47.8	71.7	140	600/750MCM 400mm ²
TL400-12	13						
TL400-14	14.5						
TL400-16	17						